

Oxygen & Argon Works Ltd.	Spec.No.G-03.004	
Product Manufacturing Control	Issue: C	Date:15.01.2009
GAS SPECIFICATION	Sheet 1 of 1	

ARGON - Ultra High Purity - 99.9995%

Typical Impurity Limits:

Oxygen:	≤ 1 ppm
Nitrogen:	≤ 2.5 ppm
Carbon Dioxide	≤ 0.5 ppm
Hydrogen:	≤ 0.2 ppm
Moisture:	≤ 1.5 ppm
T.H.C.	≤ 0.5 ppm



Above specification applies to both Argon Gas and Argon Liquid.


Quality Assurance - According to company QC procedure No. 03.04

Manufacture - According to Company Works' Instructions Nos.: 01.01, 01.02, 02.03.

Packing & Distribution - In high pressure gas cylinders, liquid DEWARS and Cryogenic road tankers according to customers' requirements.

Valve Outlet Thread - According to IS 637 part 3.
[24.5mm NGO, 14 teeth/", Female, Cylindrical, right hand (CGA580)]

Hazardous Materials Codes			
	U.N. No.	Emergency Actions	Hazard Class
GAS	1006	2T	2.2
LIQUID	1951	2T	2.2

Originator : Meir Ben Ishay	Date: 15.01.2009	Signature: 
-----------------------------	------------------	--